

UT-LEDA1921E27, UT-LEDA1921E27C

| Product code | UT-LEDA1921E27 | UT-LEDA1921E27C |
|--|----------------|-----------------|
| Classification | LED | |
| Wattage [W] | 17 | |
| Lumens [lm] | 1921 | |
| Cap / Base | E27 | |
| Claimed equivalent incandescent lamp power | 120 | |
| Beam angle [°] | 200 | |
| Rated life [h] | 15000 (25°C) | |
| Rated number of switching cycles | ≥ 7500 | |
| Warm-up time to 95% [sec] | ≤ 1 | |
| Startup time [sec] | ≤ 0,5 | |
| Operating temperature [°C] | -20...+40 | |
| Dimmable | Non-dimmable | |
| Overall length [mm] | 143 | |
| Diameter [mm] | 67 | |
| Colour temperature [Kelvin] | 3000 | 4000 |
| Colour type | Warm white | Cool white |
| Rated colour rendering index [Ra] | 80 | |
| Colour rendering group | 1B | |
| Lumen maintenance at 15000hrs | 70 | |
| Voltage [V] | 220...240 | |
| Nominal current [mA] | 150 | |
| Operating frequency [Hz] | 50...60 | |
| Power factor | 0,5 | |
| Energy efficiency class | E | |

