

DATA SHEET

**UT-LEDS600GU10,
UT-LEDS660GU10C**



| Product code | UT-LEDS600GU10 | UT-LEDS660GU10C |
|--|----------------|-----------------|
| Classification | LED | |
| Wattage [W] | 5,7 | |
| Total lumens [lm] | 600 | 660 |
| Useful lumens [lm] | 540 | 600 |
| Cap / Base | GU10 | |
| Claimed equivalent incandescent lamp power [W] | > 50 | |
| Beam angle [°] | 110 | |
| Rated life [h] | 25000 (25°C) | |
| Rated number of switching cycles | ≥ 12500 | |
| Warm-up time to 95% [sec] | ≤ 2 | |
| Startup time [sec] | ≤ 0,5 | |
| Operating temperature [°C] | -20...+40 | |
| Dimmable | Dimmable | |
| Overall length [mm] | 54 | |
| Diameter [mm] | 50 | |
| Colour temperature [Kelvin] | 3000 | 4000 |
| Colour type | Warm white | Cool white |
| Rated colour rendering index [Ra] | 80 | |
| Colour rendering group | 1B | |
| Lumen maintenance at 25000hrs [%] | 70 | |
| Voltage [V] | 220...240 | |
| Nominal current [mA] | 37 | |
| Operating frequency [Hz] | 50...60 | |
| Power factor | 0,5 | |
| Energy efficiency class | E | |

